


CHALKBOARD™

colorhouse™



INTERIOR CHALKBOARD

Product Data Sheet



DRY TIME

Dry to touch in 30-60 minutes; recoat after 8 hours. Allow 48 hours before chalking; 1 week before using a damp cloth.



COVERAGE

Covers 90 -100 square feet per quart.



CLEAN UP

Wash tools with warm soapy water. Scrape excess paint before washing.



STORAGE

Store in a dry area. Protect from freezing.



PACKAGING

Recycled content containers
100% PCW chlorine-free labels
100% PCW brochures

PROCESS

LEED® Gold manufacturing facility
Member EPA SmartWay transportation
Renewable energy at HQ

PROVEN

LEED® compliant
South Coast Air Quality
Management District - Super Compliant

VOC CONTENT STATEMENT

Maximum VOC content for untinted base paint and primer: 3 g/L (as determined by ASTM Test Method D 6886). The VOC content may increase after tinting.

VOC EMISSIONS STATEMENT

Our untinted base paints and primers have zero VOC emissions 14 days after application in a non-residential setting, based on California CDPH Standard Method Section 01350, the most popular US standard for evaluating and restricting VOC emissions for indoor air. VOC emissions may increase after tinting.

MOLD RESISTANT

Enhanced with antimicrobial protection to provide continuous protection against bacteria, mold, and mildew that cause stains and odors on the dried paint film.

SELF-PRIMING

Self-priming over surfaces previously painted with water-based paint. For the best finish over new drywall or plaster, prime with Colorhouse Multi-Purpose Primer. For best adhesion, use Colorhouse Multi-Purpose Primer painting on surfaces previously painted with oil-based paint, galvanized metal, and raw wood before top-coating.

WARRANTY All Colorhouse paint is backed by a lifetime guarantee for as long as you reside in your home. Please see www.colorhousepaint.com for complete warranty information.

USE Chalkboard paint turns any interior surface into a chalkboard. For best results, apply over smooth surfaces.

PREP Clean off dirt, dust, and other contaminants. Remove loose paint and patch holes with spackle or caulking. Dull glossy surfaces. Prime new drywall, wood, aluminum, existing oil base paint and glossy surfaces with Colorhouse Inspired Multi-Purpose Primer before painting.

APPLY Stir well. BRUSH: 2½" angle brush for the straightest lines. ROLL: We like ½" nap roller or a foam roller on smooth walls for best chalkboard results.

TIPS Allow chalkboard paint to dry for 48 hours before using the chalkboard surface. Prior to the first use, rub the entire surface with the side of a piece of chalk and then dry erase. Your chalkboard is now ready to use. Chalk residue can be removed with a damp cloth once the paint has dried for 7 days. Repeat rubbing the entire surface with the side of a piece of chalk before using again.

DISPOSAL Don't pour unused contents down the drain. This is harmful to the environment. Check www.earth911.org for recycling and disposal information.

INGREDIENT LIST (White Base) Water, 7732-18-5; Titanium Dioxide, 13463-67-7; Acrylic Resin, Proprietary; Nepheline Syenite, 37244-96-5; Calcined Kaolin, 66402-68-4

PHYSICAL PROPERTIES

WEIGHT 11.7lbs per gallon (ASTM D 1475)

RESIN TYPE 100% acrylic

FINISH 2-3% on a 60° meter, 3-4% on a 85° meter

RECOMMENDED DFT Wet: 3.7 mils, Dry: 1.5 mils

SOLIDS VOLUME 40% ± 2%,

SOLIDS WEIGHT 57% ± 2%

SHELF LIFE 2 years (unopened containers)

